

Items Supplied >

- 1 Sissy Bar w/pad
- 2 Brackets
- 4 8mm x 16mm Button head Bolts

Application(s) >

Kawasaki Vulcan 1500D/E/N 96-08

Instruction Manual >

02-4940/02-5440/02-5940

Your sissy bar will install in just a few minutes using common tools. Read all instructions carefully and completely before installing your new sissy bar.

- 1. Remove the two (2) rear bolts on each fender rail.
- 2. Install the brackets with the bent portion (part number) toward the inside using the stock bolts and tighten. Brackets will mount on the outside of fender rail.
- 3. Install the sissy bar to the brackets using the supplied 8mm x 16mm bolts and tighten.
- * Cobra recommends you always wear a helmet while riding. Please never operate your motorcycle while under the influence of alcohol and/or drugs. Enjoy the new look of your motorcycle and please ride safely.

DOCUMENT NO. 0019 REV. A. 10/03

Anything's Possible.

www.cobrausa.com

www.cobrausa.com

COBRA

23801 E. La Palma Ave., Yorba Linda, Ca 92887 Ph. 714.692.8180 Fax. 714.692.5016

Items Sunnlied >

- 1 Sissy Bar w/pad
- 2 Brackets
- 4 8mm x 16mm Button head Bolts

Annlication(s) >

Kawasaki Vulcan 1500D/E/N 96-08

Instruction Manual >

02-4940/02-5440/02-5940

Your sissy bar will install in just a few minutes using common tools. Read all instructions carefully and completely before installing your new sissy bar.

- 1. Remove the two (2) rear bolts on each fender rail.
- 2. Install the brackets with the bent portion (part number) toward the inside using the stock bolts and tighten. Brackets will mount on the outside of fender rail.
- 3. Install the sissy bar to the brackets using the supplied 8mm x 16mm bolts and tighten
- * Cobra recommends you always wear a helmet while riding. Please never operate your motorcycle while under the influence of alcohol and/or drugs. Enjoy the new look of your motorcycle and please ride safely.

DOCUMENT NO. 0019 REV. A 10/03