

# COBRA

® 23801 E. La Palma Ave., Yorba Linda, Ca 92887 Ph. 714.692.8180 Fax. 714.692.5016

[www.cobrausa.com](http://www.cobrausa.com)

## Items Supplied >

1 – Sissy Bar Rack

**\* Cobra sissy bar racks are designed to fit with Cobra sissy bars only \***

## Application(s) >

HONDA VLX600 98-08, ACE 750 98-03, SPIRIT 750 01-08,  
AERO 750 04-11, ACE1100/TOURER 95-99,  
VT1100 ALL (EXCEPT AERO), VTX1300C/R/S,  
VTX1800C/R/S/F 02-09  
KAWASAKI VULCAN 800A 95-05  
YAMAHA ROAD STAR 1600/1700 99-09

## Instruction Manual >

02-3500B

1. Working on the right hand side of the motorcycle, remove the two bolts, which secure the sissy bar to the support bracket. Set the bolts aside for reassembly.
2. Carefully slide the sissy bar rack between the support bracket and sissy bar, aligning the holes.
3. Install the bolts removed in Step 1 and finger tighten.
4. Repeat steps 1 through 3 on the left hand side of the motorcycle. Tighten bolts to 12 ft. lbs.

**To clean your black accessory use a liquid based soap detergent, such as dishwashing soap applied with a soft cloth and rinse with clean water. Note: Avoid abrasive cleaning methods such as granular or dry cleansers, simple green, Scotch-Brite or steel wool pads. Abrasives may breach the coating and shorten life.**

***\*Cobra® recommends you always wear a helmet while riding. Please never operate your motorcycle while under the influence of alcohol and/or drugs. Enjoy the new look of your motorcycle and please ride safely.***

05/14

***Anything's Possible.®***

# COBRA

® 23801 E. La Palma Ave., Yorba Linda, Ca 92887 Ph. 714.692.8180 Fax. 714.692.5016

[www.cobrausa.com](http://www.cobrausa.com)

## Items Supplied >

1 – Sissy Bar Rack

**\* Cobra sissy bar racks are designed to fit with Cobra sissy bars only \***

## Application(s) >

HONDA VLX600 98-08, ACE 750 98-03, SPIRIT 750 01-08,  
AERO 750 04-11, ACE1100/TOURER 95-99,  
VT1100 ALL (EXCEPT AERO), VTX1300C/R/S,  
VTX1800C/R/S/F 02-09  
KAWASAKI VULCAN 800A 95-05  
YAMAHA ROAD STAR 1600/1700 99-09

## Instruction Manual >

02-3500B

1. Working on the right hand side of the motorcycle, remove the two bolts, which secure the sissy bar to the support bracket. Set the bolts aside for reassembly.
2. Carefully slide the sissy bar rack between the support bracket and sissy bar, aligning the holes.
3. Install the bolts removed in Step 1 and finger tighten.
4. Repeat steps 1 through 3 on the left hand side of the motorcycle. Tighten bolts to 12 ft. lbs.

**To clean your black accessory use a liquid based soap detergent, such as dishwashing soap applied with a soft cloth and rinse with clean water. Note: Avoid abrasive cleaning methods such as granular or dry cleansers, simple green, Scotch-Brite or steel wool pads. Abrasives may breach the coating and shorten life.**

***\*Cobra® recommends you always wear a helmet while riding. Please never operate your motorcycle while under the influence of alcohol and/or drugs. Enjoy the new look of your motorcycle and please ride safely.***

05/14

***Anything's Possible.®***